

MÜLLER excavator-mounted drill drives RHA series

Type			MS-RHA123*	MS-RHA163*	MS-RHA 24 3*	MS-RHA 34 3*	MS-RHA 46 3*
Torque	M (max.)	Nm	12.000	16.000	24.000	34.000	46.000
Speed	n (max.)	min-1	30-125	30-115	30-110	30-100	30-70
Operating pressure	p (max.)	bar	80-350	80-350	80-350	80-350	80-350
Power consumption	P	kW	10-152	15-204	17-268	24-350	35-350
Required oil flow	Q motor (max.)	l/min	65-260	95-350	130-460	180-600	260-600
Diameter	Smallest drilling diameter	mm	200	200	400	400	400
Diameter	Largest drilling diameter	mm	700	900	1.200	1.400	1.600
Drill depth	With smallest drilling diameter (max.)	m	20	25	14	16	20
Drill depth	With largest drilling diameter (max.)	m	4	4	2	2	2
Weight	without auger/without stand	kg	300	360	440	600	760
Dimensions	Height H	mm	983	1.149	1.148	1.234	1.240
	Diameter D	mm	425	400	390	485	555
Hexagon connection		mm	70 / 70	70 / 80	80 / 80	100 / 100	120 / 120
Recommended excavator	Weight	t	10-20	15-25	20-30	28-40	35-50
Recommended excavator	P	kW	80-125	120-150	125-220	160-438	144-438

*Connection to excavator stick

Options available upon request: mounted on leader, clamped into vibratory hammer clamping device

